

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Roof repair spray E-COLL
- **Article number:** 4317784528467
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU21 Consumer uses: Private households / general public / consumers
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Sealing
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
 EDE Platz 1
 D-42389 Wuppertal
 Germany

 Tel. +49 202 6096-0
 e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



F+; Extremely flammable

R12: Extremely flammable.

R52/53-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02

Trade name: Roof repair spray E-COLL
















(Contd. of page 1)

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P211 Do not spray on an open flame or other ignition source.
P273 Avoid release to the environment.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 109-87-5 EINECS: 203-714-2	dimethoxymethane  F R11  Flam. Liq. 2, H225;  Acute Tox. 4, H302	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-XXXX	butane  F+ R12  Flam. Gas 1, H220; Press. Gas, H280	10-25%
CAS: 64742-82-1 EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)  Xn R65;  N R51/53 R10-66-67  Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  STOT SE 3, H336	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane  F+ R12  Flam. Gas 1, H220; Press. Gas, H280	2,5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-XXXX	isobutane  F+ R12  Flam. Gas 1, H220; Press. Gas, H280	2,5-10%

(Contd. on page 3)

Safety data sheet














according to 1907/2006/EC, Article 31

Printing date 07.07.2014

Version number 2

Revision: 07.07.2014

Trade name: Roof repair spray E-COLL

		(Contd. of page 2)
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45	aluminium powder (stabilised)  F R11  Flam. Sol. 1, H228	2,5-10%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom.  Xn R65;  Xi R37;  N R51/53 R10-66-67  Flam. Liq. 3, H226;  Asp. Tox. I, H304;  Aquatic Chronic 2, H411;  STOT SE 3, H336	2,5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119486136-34	xylene  Xn R20/21;  Xi R38 R10  Flam. Liq. 3, H226;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2,5-10%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

· **After inhalation:**

Seek medical treatment in case of complaints.

Supply fresh air.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

If symptoms persist consult doctor.

Rinse out mouth and then drink plenty of water.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.

· **5.3 Advice for firefighters**

· **Protective equipment:** Do not inhale explosion gases or combustion gases.

· **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation


(Contd. on page 4)

Trade name: Roof repair spray E-COLL

(Contd. of page 3)

- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Open and handle receptacle with care.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
 Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene

IOELV	Short-term value: 442 mg/m ³ , 100 ppm
	Long-term value: 221 mg/m ³ , 50 ppm
	Skin

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**
Not necessary if room is well-ventilated.
Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 5)

Trade name: Roof repair spray E-COLL

(Contd. of page 4)

Filter A/P2

· **Protection of hands:**



Protective gloves

· **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0,4$ mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Brown

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 235 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

Lower: 0,7 Vol %

Upper: 17,6 Vol %

· **Vapour pressure at 20 °C:** 2800 hPa

· **Density at 20 °C:** 0,74 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 6)

Trade name: Roof repair spray E-COLL

(Contd. of page 5)

- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
 - Organic solvents:** 87,6 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with oxidizing agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

64742-82-1 Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Oral LD50 >15000 mg/kg (rat) (OECD 401)

Dermal LD50 ~3400 mg/kg (rat) (OECD 402)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6800 mg/kg (rat)

Dermal LD50 >3400 mg/kg (rab)

- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
 - **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
 - Harmful to aquatic organisms
 - Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

(Contd. on page 7)

Trade name: Roof repair spray E-COLL

(Contd. of page 6)

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· **European waste catalogue**

15 01 10*	packaging containing residues of or contaminated by dangerous substances
15 01 04	metallic packaging

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1950

· **14.2 UN proper shipping name**

· **ADR** UN1950 AEROSOLS
· **IMDG, IATA** AEROSOLS

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2 5F Gases.
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2 Gases.
· **Label** 2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Gases.

· **EMS Number:** F-D,S-U

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L
· **Transport category** 2
· **Tunnel restriction code** D

(Contd. on page 8)

Trade name: Roof repair spray E-COLL

(Contd. of page 7)

· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.
- **Exposure scenario(s)**
Exposure scenario(s) of ingredients (if present) are available on request at:
sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- R37 Irritating to respiratory system.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - Flam. Gas 1: Flammable gases, Hazard Category 1
 - Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
 - Press. Gas: Gases under pressure: Compressed gas
 - Flam. Liq. 2: Flammable liquids, Hazard Category 2
 - Flam. Liq. 3: Flammable liquids, Hazard Category 3
 - Flam. Sol. 1: Flammable solids, Hazard Category 1
 - Acute Tox. 4: Acute toxicity, Hazard Category 4
 - Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 - STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
 - Asp. Tox. 1: Aspiration hazard, Hazard Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
 - Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3
- *** Data compared to the previous version altered.**