

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *FORMAT Marking spray for construction sites*
- **Article number:**
4317784346962, 4317784158701, 4317784158718, 4317784158725, 4317784158732, 4317784158749,
4317784158756, 4317784158763, 4317784158770
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** *Paint*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
EDE Platz 1
D-42389 Wuppertal
Germany
-
- Tel. +49 202 6096-0*
e-mail: sdb@ede.de
- **Further information obtainable from:** *Product safety department*
- **1.4 Emergency telephone number:** *Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Irritant

R36: Irritating to eyes.



F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurised container.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Trade name: FORMAT Marking spray for construction sites

(Contd. of page 1)

· **2.2 Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xi Irritant
F+ Extremely flammable

· **Risk phrases:**

- 12 Extremely flammable.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

- 2 Keep out of the reach of children.
- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe spray.
- 24/25 Avoid contact with skin and eyes.
- 51 Use only in well-ventilated areas.
- 56 Dispose of this material and its container to hazardous or special waste collection point.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

· **Classification in accordance with Directive 75/324/EEC: Extremely flammable**

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**







- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx	acetone  R66-67 <hr style="border-top: 1px dashed #000;"/> 	25-50%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate  R66-67 <hr style="border-top: 1px dashed #000;"/> 	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-XXXX	butane  <hr style="border-top: 1px dashed #000;"/> 	10-25%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.08.2014

Version number 2


Revision: 27.08.2014


Trade name: *FORMAT Marking spray for construction sites*

EINECS: 200-827-9

Index number: 601-003-00-5

propane

 F+ R12

 Flam. Gas 1, H220; Press. Gas, H280

(Contd. of page 2)

10-25%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Open and handle receptacle with care.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.



Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

Trade name: FORMAT Marking spray for construction sites

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Protect from heat and direct sunlight.
- **Storage class:** -
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

IOELV Long-term value: 1210 mg/m ³ , 500 ppm
--

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

- **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation - filter AX.

- **Protection of hands:** Recommendation: protective gloves

- **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0,4$ mm

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Aerosol

Colour: Various colours

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -44 °C

- **Flash point:** -97 °C

- **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 5)

Trade name: FORMAT Marking spray for construction sites

(Contd. of page 4)

· Ignition temperature:	365 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1,5 Vol %
Upper:	13,0 Vol %
· Vapour pressure at 20 °C:	2800 hPa
· Density at 20 °C:	0,75 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
VOC (EC)	675,0 g/l
VOCV (CH)	90,00 %
Solids content:	10,0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity:**
 - **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** Irritating effect.
 - **Sensitisation:** No sensitising effects known.
 - **Additional toxicological information:**
- The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
- Irritant

EU

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.08.2014

Version number 2

Revision: 27.08.2014

Trade name: FORMAT Marking spray for construction sites

(Contd. of page 5)

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.
- **Recommendation**
Completely emptied packagings can be given for recycling. (In accordance with local authority regulations, take to chemical/physical treatment plant.)

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** UN1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 2 5F Gases.
- **Label** 2.1

- **IMDG, IATA**



- **Class** 2.1

(Contd. on page 7)

Trade name: FORMAT Marking spray for construction sites

(Contd. of page 6)

· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Gases. - F-D,S-U
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code	1L 2 D
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- R11 Highly flammable.
- R12 Extremely flammable.
- R36 Irritating to eyes.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

- **Department issuing MSDS:** Product safety department

- **Contact:** Head of Product Safety Department

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)
- VOC: Volatile Organic Compounds (USA, EU)
- Flam. Gas 1: Flammable gases, Hazard Category 1
- Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas: Gases under pressure: Compressed gas
- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3