

Printing date 07.07.2014 Version number 201 Revision: 07.07.2014

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Power spray adhesive E-COLL
- · Article number: 4317784528450
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH

EDE Platz 1

D-42389 Wuppertal

Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



#### GHS07

Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	Н336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36/38: Irritating to eyes and skin.



F+; Extremely flammable

R12: Extremely flammable.

R52/53-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)



Printing date 07.07.2014 Version number 2 Revision: 07.07.2014

Trade name: Power spray adhesive E-COLL

(Contd. of page 1)

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

#### · Signal word Danger

### · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light methyl acetate

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

*H412 Harmful to aquatic life with long lasting effects.* 

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*P251* Do not pierce or burn, even after use.

*P260 Do not breathe spray.* 

*P211* Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

#### · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

(Contd. on page 3)



Printing date 07.07.2014 Version number 2 Revision: 07.07.2014

Trade name: Power spray adhesive E-COLL

CAS: 79-20-9	methyl acetate	25-50%
EINECS: 201-185-2	<b>X</b> i R36; <b>№</b> F R11	
Index number: 607-021-00-X	R66-67	
	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 106-97-8	butane	10-25%
EINECS: 203-448-7	▶ F+ R12	
Index number: 601-004-00-0	Flam. Gas 1, H220; Press. Gas, H280	
Reg.nr.: 01-2119474691-32-XXXX	·	
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	10-25%
EINECS: 265-151-9	<b>X</b> Xn R65; <b>X</b> Xi R38; <b>№</b> F R11; <b>№</b> N R51/53	
Index number: 649-328-00-1	R67	
Reg.nr.: 01-2119475133-43-XXXX	🚸 Flam. Liq. 2, H225; 🗞 Asp. Tox. 1, H304; 🕸 Aquatic	
	Čhronic 2, Ĥ411; 🔥 Skiň Irrît. 2, H315; STOT ŠE 3, H336	
CAS: 74-98-6	propane	2,5-10%
EINECS: 200-827-9	<b>♦</b> F+ R12	
Index number: 601-003-00-5	🚸 Flam. Gas 1, H220; Press. Gas, H280	
Reg.nr.: 01-2119486944-21-xxxx		
EC number: 921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-	2,5-10%
Reg.nr.: 01-2119475515-33-xxxx	hexane	
	Xn R65; Xi R38;	
	♠ Flam. Liq. 1, H224; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ↑ Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 75-28-5	isobutane	2,5-10%
EINECS: 200-857-2	<b>▶</b> F+ R12	
Index number: 601-004-00-0	Flam. Gas 1, H220; Press. Gas, H280	
Reg.nr.: 01-2119485395-27-XXXX		

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

· After inhalation:

Seek medical treatment in case of complaints.

Supply fresh air.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Rinse out mouth and then drink plenty of water.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

 $No\ further\ relevant\ information\ available.$ 

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.

(Contd. on page 4)



Printing date 07.07.2014 Version number 2 Revision: 07.07.2014

Trade name: Power spray adhesive E-COLL

(Contd. of page 3)

- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle receptacle with care.

Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)



Printing date 07.07.2014 Version number 2 Revision: 07.07.2014

Trade name: Power spray adhesive E-COLL

(Contd. of page 4)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Protection of hands:



Protective gloves

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:

Form:
Colour:
Odour:
Odour threshold:
PH-value:

Aerosol
Yellowish
Characteristic
Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 365 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Not determined.

· Explosion limits:

**Lower:** 0,9 Vol %

(Contd. on page 6)



Printing date 07.07.2014 Version number 2 Revision: 07.07.2014

Trade name: Power spray adhesive E-COLL

		(Contd. of page 5
Upper:	16,0 Vol %	
· Vapour pressure at 20 °C:	4000 hPa	
Density at 20 °C:	$0.72 \text{ g/cm}^3$	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	vater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Organic solvents:	82,0 %	
· 9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with oxidizing agents.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

## SECTION 12: Ecological information

- · 12.1 Toxicity
- $\cdot \textbf{\textit{Aquatic toxicity:}} \ \textit{No further relevant information available}.$
- · 12.2 Persistence and degradability No further relevant information available.
- $\cdot \textbf{12.3 Bioaccumulative potential} \ No \ further \ relevant \ information \ available.$
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

(Contd. on page 7)



Printing date 07.07.2014 Version number 2 Revision: 07.07.2014

Trade name: Power spray adhesive E-COLL

(Contd. of page 6)

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European	waste catalogue
15 01 10*	packaging containing residues of or contaminated by dangerous substances
15 01 04	metallic packaging

**UN1950 AEROSOLS** 

2 5F Gases.

SECTION .	14.	Transport	inform	nation
DECITOR	LT.	Transport	uijoin	imion

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1950
- · 14.2 UN proper shipping name
- · IMDG, IATA **AEROSOLS**
- · 14.3 Transport hazard class(es)
- $\cdot ADR$



- · Class
- · Label
- · IMDG, IATA



- 2 Gases. · Class · Label 2.1
- · 14.4 Packing group
- · ADR, IMDG, IATA Void
- · 14.5 Environmental hazards:
- · Marine pollutant: No
- · 14.6 Special precautions for user Warning: Gases.
- F-D,S-U· EMS Number:
- · 14.7 Transport in bulk according to Annex II of
- MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 8)



Printing date 07.07.2014 Version number 2 Revision: 07.07.2014

Trade name: Power spray adhesive E-COLL

	(Contd. of page 7)
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	IL
· Transport category	2
· Tunnel restriction code	D
· UN ''Model Regulation'':	UN1950, AEROSOLS, 2.1

## SECTION 15: Regulatory information

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Exposure scenario(s)

 $\label{present} \textit{Exposure scenario}(s) \ of \ ingredients \ (\textit{if present}) \ are \ available \ on \ request \ at:$ 

sdb@ede.de

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R12 Extremely flammable.
- R36 Irritating to eyes.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Flam. Liq. 1: Flammable liquids, Hazard Category 1

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

\* \* Data compared to the previous version altered.