

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PU sealant E-COLL
- **Article number:** 4317784150712, 4317784150705, 4317784150767
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU21 Consumer uses: Private households / general public / consumers
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Sealant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
 EDE Platz 1
 D-42389 Wuppertal
 Germany

 Tel. +49 202 6096-0
 e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Sensitising

R42: May cause sensitisation by inhalation.

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
methylenediphenyl diisocyanate
- **Hazard statements**
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Trade name: PU sealant E-COLL

(Contd. of page 1)

- P102 Keep out of reach of children.
 P284 [In case of inadequate ventilation] wear respiratory protection.
 P261 Avoid breathing vapours.
 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
Contains isocyanates. May produce an allergic reaction.
 - **2.3 Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene ☒ Xn R20; ☒ F R11 ☒ Flam. Liq. 2, H225; ☒ STOT RE 2, H373; Asp. Tox. 1, H304; ☒ Acute Tox. 4, H332	2.5-10%
CAS: 90989-38-1 EINECS: 292-694-9 Reg.nr.: 01-2119486136-34-xxxx	Aromatic hydrocarbons, C8 ☒ Xn R20/21-65; ☒ Xi R38 R10 ☒ Flam. Liq. 3, H226; ☒ Asp. Tox. 1, H304; ☒ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%
CAS: 26447-40-5 EINECS: 247-714-0	methylenediphenyl diisocyanate ☒ Xn R20-40-48/20; ☒ Xn R42/43; ☒ Xi R36/37/38 Carc. Cat. 3 ☒ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ☒ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	< 1%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Personal protection for the First Aider.
- **After inhalation:**
Supply fresh air.
Seek medical treatment in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Seek immediate medical advice.
Rinse out mouth and then drink plenty of water.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Trade name: PU sealant E-COLL

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide (CO)
Sulphur dioxide (SO₂)
Hydrogen chloride (HCl)
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear fully protective suit.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Provide floor trough without outlet.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class:** -
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

Trade name: PU sealant E-COLL

(Contd. of page 3)

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm
	Long-term value: 441 mg/m ³ , 100 ppm
Sk	

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation - filter A2-P2.

· **Protection of hands:**



Protective gloves

· **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Recommendation: safety glasses with side protection shield

· **Body protection:** Impervious protective clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Viscous
· Colour:	Different according to colouring
· Odour:	Solvent-like
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	Undetermined.

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 500 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

· **Lower:** 1.1 Vol %

(Contd. on page 5)

Trade name: PU sealant E-COLL

(Contd. of page 4)

Upper:	7.0 Vol %
· Vapour pressure at 20 °C:	6.7 hPa
· Density at 20 °C:	1.3 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
VOC (EC) %	6.00 %
VOC (EC) g/l	78.0 g/l
VOCV (CH)	6.00 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Sulphur oxides (SO_x)
Hydrogen chloride (HCl)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitisation:** Sensitisation possible through inhalation.
- **Other information (about experimental toxicology):**
Persons already sensitised to isocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A).
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

GB

(Contd. on page 6)

Trade name: PU sealant E-COLL

(Contd. of page 5)

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste.
Observe local regulations.

- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances
15 01 10*	packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

- | | |
|---|-----------------|
| · 14.1 UN-Number
· ADR, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name
· ADR
· ADN, IMDG, IATA | UN-
Void |
| · 14.3 Transport hazard class(es)
· ADR, ADN, IMDG, IATA
· Class | Void |
| · 14.4 Packing group
· ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards:
· Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | UN-, - |

GB

(Contd. on page 7)

Trade name: PU sealant E-COLL

(Contd. of page 6)

SECTION 15: Regulatory information

- **National regulations:**
- **Information about limitation of use:**
Employment restrictions concerning pregnant and lactating women must be observed.
- **15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 *Highly flammable liquid and vapour.*
 - H226 *Flammable liquid and vapour.*
 - H304 *May be fatal if swallowed and enters airways.*
 - H312 *Harmful in contact with skin.*
 - H315 *Causes skin irritation.*
 - H317 *May cause an allergic skin reaction.*
 - H319 *Causes serious eye irritation.*
 - H332 *Harmful if inhaled.*
 - H334 *May cause allergy or asthma symptoms or breathing difficulties if inhaled.*
 - H335 *May cause respiratory irritation.*
 - H351 *Suspected of causing cancer.*
 - H373 *May cause damage to organs through prolonged or repeated exposure.*
-
- R10 *Flammable.*
 - R11 *Highly flammable.*
 - R20 *Harmful by inhalation.*
 - R20/21 *Harmful by inhalation and in contact with skin.*
 - R36/37/38 *Irritating to eyes, respiratory system and skin.*
 - R38 *Irritating to skin.*
 - R40 *Limited evidence of a carcinogenic effect.*
 - R42/43 *May cause sensitisation by inhalation and skin contact.*
 - R48/20 *Harmful: danger of serious damage to health by prolonged exposure through inhalation.*
 - R65 *Harmful: may cause lung damage if swallowed.*

- **Department issuing MSDS:** *Product safety department*

- **Contact:** *Head of Product Safety Department*

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: International Maritime Code for Dangerous Goods*
- IATA: International Air Transport Association*
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals*
- EINECS: European Inventory of Existing Commercial Chemical Substances*
- ELINCS: European List of Notified Chemical Substances*
- CAS: Chemical Abstracts Service (division of the American Chemical Society)*
- VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)*
- VOC: Volatile Organic Compounds (USA, EU)*
- Flam. Liq. 2: Flammable liquids, Hazard Category 2*
- Flam. Liq. 3: Flammable liquids, Hazard Category 3*
- Acute Tox. 4: Acute toxicity, Hazard Category 4*
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2*
- Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1*
- Skin Sens. 1: Sensitisation - Skin, Hazard Category 1*
- Carc. 2: Carcinogenicity, Hazard Category 2*
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*
- STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2*
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1*