

## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Rust primer, grey E-COLL
- **Article number:** 4317784305334, 4317784305310
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Anticorrosion additive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH  
EDE Platz 1  
D-42389 Wuppertal  
Germany  
  
Tel. +49 202 6096-0  
e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

## 2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2      H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

R10-52/53-67: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02    GHS07

- **Signal word** Warning

**Trade name: Rust primer, grey E-COLL**

(Contd. of page 1)

· **Hazard statements**

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves / eye protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Contains 2-butanone oxime. May produce an allergic reaction.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

|  |  |         |
|--|--|---------|
| EC number: 918-668-5<br>Reg.nr.: 01-2119455851-35-xxxx   | Solvent naphtha (petroleum), light arom.<br>☒ Xn R65; ☒ Xi R37; ☒ N R51/53<br>R10-66-67<br>-----<br>☠ Flam. Liq. 3, H226; ☠ Asp. Tox. 1, H304; ☠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336 | 10-25%  |
| CAS: 1330-20-7<br>EINECS: 215-535-7<br>Index number: 601-022-00-9<br>Reg.nr.: 01-2119486136-34     | xylene<br>☒ Xn R20/21; ☒ Xi R38<br>R10<br>-----<br>☠ Flam. Liq. 3, H226; ☠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315   | 10-25%  |
| CAS: 107-98-2<br>EINECS: 203-539-1<br>Index number: 603-064-00-3<br>Reg.nr.: 01-2119457435-35-xxxx | 1-methoxy-2-propanol<br>R10-67<br>-----<br>☠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336   | 2,5-10% |
| CAS: 96-29-7<br>EINECS: 202-496-6<br>Index number: 616-014-00-0<br>Reg.nr.: 01-2119539477-28-xxxx  | 2-butanone oxime<br>☒ Xn R21-40; ☒ Xi R41; ☒ Xi R43<br>Carc. Cat. 3<br>-----<br>☠ Carc. 2, H351; ☠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H312; Skin Sens. 1, H317                                    | < 1%    |

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.  
Personal protection for the First Aider.

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

**Trade name: Rust primer, grey E-COLL**

(Contd. of page 2)

- Seek medical treatment in case of complaints.
- Supply fresh air.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**  
If symptoms persist consult doctor.  
Rinse out mouth and then drink plenty of water.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store only in the original receptacle.  
Provide floor trough without outlet.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 4)

**Trade name: Rust primer, grey E-COLL**

(Contd. of page 3)

- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

### 1330-20-7 xylene

|          |   |
|----------|---|
| IOELV () | Short-term value: 442 mg/m <sup>3</sup> , 100 ppm |
|          | Long-term value: 221 mg/m <sup>3</sup> , 50 ppm   |
|          | Skin  |

### 107-98-2 1-methoxy-2-propanol

|          |   |
|----------|---|
| IOELV () | Short-term value: 568 mg/m <sup>3</sup> , 150 ppm |
|          | Long-term value: 375 mg/m <sup>3</sup> , 100 ppm  |
|          | Skin  |

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Avoid contact with the eyes and skin.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation - filter A2
- **Protection of hands:**



Protective gloves

- **Material of gloves**  
Nitrile rubber, NBR  
Recommended thickness of the material: ≥ 0,4 mm
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Recommendation: safety glasses with side protection shield
- **Body protection:** Use protective suit.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

|                         |                 |
|-------------------------|-----------------|
| <b>Form:</b>            | Fluid           |
| <b>Colour:</b>          | Grey            |
| <b>Odour:</b>           | Characteristic  |
| <b>Odour threshold:</b> | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

|                                     |               |
|-------------------------------------|---------------|
| <b>Melting point/Melting range:</b> | Undetermined. |
| <b>Boiling point/Boiling range:</b> | > 100 °C      |

(Contd. on page 5)

**Trade name: Rust primer, grey E-COLL**

(Contd. of page 4)

|   |   |
|---|---|
| · <b>Flash point:</b>                             | 24 °C   |
| · <b>Flammability (solid, gaseous):</b>           | Not applicable.   |
| · <b>Ignition temperature:</b>                    | 450 °C  |
| · <b>Decomposition temperature:</b>               | Not determined.   |
| · <b>Self-igniting:</b>                           | Product is not selfigniting.  |
| · <b>Danger of explosion:</b>                     | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · <b>Explosion limits:</b>                        |   |
| <b>Lower:</b>                                     | 0,7 Vol %   |
| <b>Upper:</b>                                     | 7,5 Vol %   |
| · <b>Vapour pressure at 20 °C:</b>                | 6,7 hPa   |
| · <b>Density at 20 °C:</b>                        | 1,5 g/cm <sup>3</sup>   |
| · <b>Relative density</b>                         | Not determined.   |
| · <b>Vapour density</b>                           | Not determined.   |
| · <b>Evaporation rate</b>                         | Not determined.   |
| · <b>Solubility in / Miscibility with water:</b>  | Not miscible or difficult to mix.   |
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined.   |
| · <b>Viscosity:</b>                               |   |
| <b>Dynamic:</b>                                   | Not determined.   |
| <b>Kinematic at 20 °C:</b>                        | 60 s (DIN 53211/4)  |
| <b>Organic solvents:</b>                          | 34,0 %  |
| · <b>Other information</b>                        | No further relevant information available.  |

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with acids, alkalis and oxidizing agents.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

**Solvent naphtha (petroleum), light arom.**

Oral LD50 >6800 mg/kg (rat)

Dermal LD50 >3400 mg/kg (rab)

**1330-20-7 xylene**

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.

(Contd. on page 6)

**Trade name: Rust primer, grey E-COLL**

(Contd. of page 5)

- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.


## 13 Disposal considerations

- **Waste treatment methods**  
Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste.  
Observe local regulations.

- **European waste catalogue**

|           |   |
|-----------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances |
|-----------|---|

## 14 Transport information

- |   |                      |
|---|----------------------|
| · <b>UN-Number</b>  | UN1263               |
| · <b>ADR, IMDG, IATA</b>  |                      |
| · <b>UN proper shipping name</b>  | UN1263 PAINT         |
| · <b>ADR</b>  | UN1263 PAINT         |
| · <b>IMDG, IATA</b>   | PAINT                |
| · <b>Transport hazard class(es)</b>   |                      |
| · <b>ADR, IMDG, IATA</b>  |                      |
|  |                      |
| · <b>Class</b>  | 3 Flammable liquids. |
| · <b>Label</b>  | 3                    |

(Contd. on page 7)

**Trade name: Rust primer, grey E-COLL**

(Contd. of page 6)

|   |   |
|---|---|
| · <b>Packing group</b><br>· <b>ADR, IMDG, IATA</b>  | <b>III</b>  |
| · <b>Environmental hazards:</b><br>· <b>Marine pollutant:</b>   | <b>No</b>   |
| · <b>Special precautions for user</b><br>· <b>Danger code (Kemler):</b><br>· <b>EMS Number:</b>                     | <b>Warning: Flammable liquids.</b><br><b>30</b><br><b>F-E,S-E</b> |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>                                    | <b>Not applicable.</b>  |
| · <b>Transport/Additional information:</b>  |   |
| · <b>ADR</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Transport category</b><br>· <b>Tunnel restriction code</b> | <b>5L</b><br><b>3</b><br><b>D/E</b>                               |
| · <b>UN "Model Regulation":</b>   | <b>UN1263, PAINT, 3, III</b>                                      |

### 15 Regulatory information

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Relevant phrases**

- H226 *Flammable liquid and vapour.*
- H304 *May be fatal if swallowed and enters airways.*
- H312 *Harmful in contact with skin.*
- H315 *Causes skin irritation.*
- H317 *May cause an allergic skin reaction.*
- H318 *Causes serious eye damage.*
- H332 *Harmful if inhaled.*
- H335 *May cause respiratory irritation.*
- H336 *May cause drowsiness or dizziness.*
- H351 *Suspected of causing cancer.*
- H411 *Toxic to aquatic life with long lasting effects.*
- R10 *Flammable.*
- R20/21 *Harmful by inhalation and in contact with skin.*
- R21 *Harmful in contact with skin.*
- R37 *Irritating to respiratory system.*
- R38 *Irritating to skin.*
- R40 *Limited evidence of a carcinogenic effect.*
- R41 *Risk of serious damage to eyes.*
- R43 *May cause sensitisation by skin contact.*
- R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
- R65 *Harmful; may cause lung damage if swallowed.*
- R66 *Repeated exposure may cause skin dryness or cracking.*
- R67 *Vapours may cause drowsiness and dizziness.*

- **Department issuing MSDS:** Product safety department
- **Contact:** Head of Product Safety Department

(Contd. on page 8)

**Trade name: Rust primer, grey E-COLL**

(Contd. of page 7)

· **Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonized System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*Flam. Liq. 3: Flammable liquids, Hazard Category 3*

*Acute Tox. 4: Acute toxicity, Hazard Category 4*

*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1*

*Skin Sens. 1: Sensitisation - Skin, Hazard Category 1*

*Carc. 2: Carcinogenicity, Hazard Category 2*

*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*

*Asp. Tox. 1: Aspiration hazard, Hazard Category 1*

*Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2*

*Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3*

· **\* Data compared to the previous version altered.**