






## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 1-K Anti-Rust Primer E-COLL
- **Article number:** 4317784305495, 4317784305488
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
 SU21 Consumer uses: Private households / general public / consumers  
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Anticorrosion additive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH  
 EDE Platz 1  
 D-42389 Wuppertal  
 Germany  
  
 Tel. +49 202 6096-0  
 e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- 
GHS02 flame  
  
 Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- 
GHS05 corrosion  
  
 Eye Dam. 1 H318 Causes serious eye damage.
- 
GHS07  
  
 Skin Irrit. 2 H315 Causes skin irritation.

---

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**
- 

  
 GHS02 GHS05
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
 butan-1-ol
- **Hazard statements**  
 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.08.2015

Version number 302

Revision: 28.08.2015

**Trade name: I-K Anti-Rust Primer E-COLL**

(Contd. of page 1)

**Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P251 Do not pierce or burn, even after use.  
 P211 Do not spray on an open flame or other ignition source.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

- EUH066 Repeated exposure may cause skin dryness or cracking.  
 Buildup of explosive mixtures possible without sufficient ventilation.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1, H220; Press. Gas C, H280	25-50%
CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-10%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.5-10%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-10%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	2.5-10%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%

(Contd. on page 3)

Trade name: **1-K Anti-Rust Primer E-COLL**

(Contd. of page 2)

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

#### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Personal protection for the First Aider.  
Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air.  
Seek medical treatment in case of complaints.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.  
Seek immediate medical advice.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Do not inhale explosion gases or combustion gases.  
Mouth respiratory protective device.

· **Additional information**

Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents  
Dispose contaminated material as waste according to item 13.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**Trade name: I-K Anti-Rust Primer E-COLL**

(Contd. of page 3)

### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Open and handle receptacle with care.

Use only in well ventilated areas.

· **Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:** Store away from oxidising agents.

· **Further information about storage conditions:**

Keep container tightly sealed.

Protect from heat and direct sunlight.

· **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**115-10-6 dimethyl ether**

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

**108-10-1 4-methylpentan-2-one**

WEL Short-term value: 416 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 208 mg/m<sup>3</sup>, 50 ppm  
Sk, BMGV

**67-64-1 acetone**

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

**1330-20-7 xylene**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

**123-86-4 n-butyl acetate**

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

**71-36-3 butan-1-ol**

WEL Short-term value: 154 mg/m<sup>3</sup>, 50 ppm  
Sk

(Contd. on page 5)

**Trade name: I-K Anti-Rust Primer E-COLL**

(Contd. of page 4)

**141-78-6 ethyl acetate**

WEL Short-term value: 400 ppm  
Long-term value: 200 ppm

**100-41-4 ethylbenzene**

WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Sk

**78-93-3 butanone**

WEL Short-term value: 899 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 600 mg/m<sup>3</sup>, 200 ppm  
Sk, BMGV

· **Ingredients with biological limit values:****108-10-1 4-methylpentan-2-one**

BMGV 20 µmol/L  
Medium: urine  
Sampling time: post shift  
Parameter: 4-methylpentan-2-one

**1330-20-7 xylene**

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

**78-93-3 butanone**

BMGV 70 µmol/L  
Medium: urine  
Sampling time: post shift  
Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and feed.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter AX

· **Protection of hands:**

Protective gloves

· **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

**Trade name: I-K Anti-Rust Primer E-COLL**

(Contd. of page 5)

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Aerosol
· <b>Colour:</b>	Red-brown
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 235 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

· <b>Lower:</b>	3.0 Vol %
· <b>Upper:</b>	18.6 Vol %

· **Vapour pressure at 20 °C:** 4000 hPa

· **Density at 20 °C:** 0.84 g/cm<sup>3</sup>

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· <b>Dynamic:</b>	Not determined.
· <b>Kinematic:</b>	Not determined.
· <b>VOC (EC) %</b>	90.35 %
· <b>VOC (EC) g/l</b>	697.2 g/l
· <b>VOCV (CH)</b>	90.35 %

· **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

(Contd. on page 7)

**Trade name: I-K Anti-Rust Primer E-COLL**

(Contd. of page 6)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

#### 100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods:**  
Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste.  
Observe local regulations.

(Contd. on page 8)

**Trade name: I-K Anti-Rust Primer E-COLL**

(Contd. of page 7)

· *European waste catalogue*

15 01 10\* | packaging containing residues of or contaminated by dangerous substances

**SECTION 14: Transport information**

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1950

· **14.2 UN proper shipping name**

· **ADR** UN1950 AEROSOLS  
 · **IMDG** AEROSOLS  
 · **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2 5F Gases.  
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1  
 · **Label** 2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

· **Danger code (Kemler):** Warning: Gases.  
 · **EMS Number:** -  
F-D,S-U

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L  
 · **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity

· **Transport category**

2

· **Tunnel restriction code**

D

· **IMDG**

· **Limited quantities (LQ)** 1L  
 · **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1



**Trade name: I-K Anti-Rust Primer E-COLL**

(Contd. of page 8)

### SECTION 15: Regulatory information

- *Directive 2012/18/EU*
- *Named dangerous substances - ANNEX I None of the ingredients is listed.*
- *Seveso category P3a FLAMMABLE AEROSOLS*
- *Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t*
- *Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t*
- *National regulations:*
- *Information about limitation of use:*  
*Employment restrictions concerning pregnant and lactating women must be observed.*
- **15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

### SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Relevant phrases**  
*H220 Extremely flammable gas.*  
*H225 Highly flammable liquid and vapour.*  
*H226 Flammable liquid and vapour.*  
*H280 Contains gas under pressure; may explode if heated.*  
*H302 Harmful if swallowed.*  
*H304 May be fatal if swallowed and enters airways.*  
*H312 Harmful in contact with skin.*  
*H315 Causes skin irritation.*  
*H318 Causes serious eye damage.*  
*H319 Causes serious eye irritation.*  
*H332 Harmful if inhaled.*  
*H335 May cause respiratory irritation.*  
*H336 May cause drowsiness or dizziness.*  
*H373 May cause damage to organs through prolonged or repeated exposure.*
- **Abbreviations and acronyms:**  
*Flam. Gas 1: Flammable gases, Hazard Category 1*  
*Aerosol 1: Flammable aerosols, Hazard Category 1*  
*Press. Gas C: Gases under pressure: Compressed gas*  
*Flam. Liq. 2: Flammable liquids, Hazard Category 2*  
*Flam. Liq. 3: Flammable liquids, Hazard Category 3*  
*Acute Tox. 4: Acute toxicity, Hazard Category 4*  
*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*  
*Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1*  
*Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2*  
*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*  
*STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2*  
*Asp. Tox. 1: Aspiration hazard, Hazard Category 1*